

TT 3023 G

TECHNICAL CHARACTERISTICS OF RUBBER COATED FABRIC

	Unit	Norm	Value	Tolerance
Weight	g/sqmt	UNI EN ISO 2286-2	2900	+/- 300
Gauge	mm	UNI EN ISO 2286-3	2.40	+/-0,25
Tensile strength warp & weft	N/5cm	UNI EN ISO 1421	≥7000 / ≥7000	
Elongation at break warp & weft	%	UNI EN ISO 1421	≤38 / ≤38	
Coating fabric/adhesion	N/5cm	Int. Novurania I0396	≥ 100	
Working temperature	°C		-20 +90	
State of delivery			cured	

CHARACTERISTICS OF TEXTILE REINFORCEMENT

	Unit	Value
Type of yarn		PA
Weight	g/sqmt	500
Construction	dtex	1880 13 x 13

CHARACTERISTICS OF COATING ELASTOMER

Type of polymer	CSM (side A) – CR (side B)
Colour	medium grey (side A) – black (side B)

APPLICATIONS

Nautical applications, Hovercraft

PROVISIONAL DATA SHEET

Novurania declines any responsibility for any damage or problem coming from a wrong usage of the product.

Issuing date 22th of April 2015

Revision: 0